

FO splice housing extendable OVA 19" 1U



FO patch panel extendable with quick lock and exchangeable front panel for up to 48 fibers. For SC / LC and E2000® couplings the front panel is also supplied with screw holes in order to affix couplings. The extendible depth of 200mm ensures comfortable access to the couplings. The splice cassette holder can be loaded with up to a maximum of 4 cassettes and secured with stud bolts. The splice protectors (crimp or fusion splice protector) and their holders are not included in delivery and must be ordered separately.

Our splice boxes are available in two different versions: In variant 1, the pigtails are inserted and loaded. In variant 2, the pigtails are ready for splicing, inserted and loaded.

The pigtails are dyed per VDE color coding in the primary and secondary coating. The box can also be offset by 40 mm towards the rear. Cable entry via cable gland (special accessory).

- Full metal design
- 40 mm offsetable towards rear
- Powder coated, color RAL 7035
- Cover metallic luster
- Dimensions (HxWxD): 44.45 x 483 x 230 mm
- When open, the box can be tilted downwards

| | |
|---|---------|
| Splice holder (crimp splice protector) | LVZ0003 |
| Crimp splice protector | LVZ0005 |
| Splice holder (fusion splice protector) | LVZ0004 |
| Fusion Splice Protector | LVZ0006 |
| Fusion splice protector and holder not included in delivery (please order separately). Additional loaded variants and connector systems on request | |